

DATA SHEET

REPLACEMENT FIBERGLASS ROD GF3 Ø 3MM

Cable pulling system for pipe diameter 10 - 50 mm

Item no. **20816** | **20817** | **20818**



VIDEO
GF3
Click here Video

Click here Productinformation

Repair instructions:

1.

2.

INFO:

Front End: Guiding head with swivel and RTG Ø 6 mm front thread with kink-protection

Rear end: Kink protection with RTG Ø 6 mm inner thread

DATA			
ITEM NO.	20816	20817	20818
LENGTH	20 m	30 m	50 m
WEIGHT	0,25 kg	0,35 kg	0,55 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE Ø	optimal from 10 mm - 50 mm		
DIMENSION	H: 30 mm x DM 400 mm		
EAN-CODE	9120045477184	9120045477191	9120045477207

ADVANTAGES

- ✓ Guiding head with swivel and kink protection
- ✓ Shear-stable
- ✓ Also for occupied pipes
- ✓ Bending radius 38 mm
- ✓ Total breaking load 130 kg

Rod	rec. pipe diameter	Bending radius w.e.joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	10 - 50 mm	38 mm	28 mm	450 kg	130 kg
0,118"	0,394" - 1,969"	1,102"	1,102"	992,08 lbs	286,60 lbs

DESCRIPTION

Replacement glass fibre rod GF3 Ø 3 mm with kink protection ending joint made of stainless steel and guiding head with twist adjustment and pulling eye Ø 7 mm with RTG Ø 6 mm thread. The specified total breaking load of 130 kg always refers to the entire product (glass fibre rod incl. kink protection ending joints).

Optimal field of application: for pipe dimension 10 mm - 50 mm.

Scope of supply: 1 x Replacement glass fibre rod GF3 Ø 3 mm, length: 20 m, kink-protection-ending joint on both side (Beginning/ Ending), 1 x guiding head with twist adjustment, 1 x pulling eye Ø 7 mm, 2 x mounting-wrenches

INFORMATION

Matching products

GF3 Ø 3 mm
10192 / 10193 / 10195
20 m / 30 m / 50 m

Repairing Kit
20819

Click here Productinformation

Click here Productinformation