

DATA SHEET

FIBERGLASS ROD Ø 6 MM STANDARD-SET

with steel cage incl. new double run-out system

Item no.: 10060 | 10062 | 10064 | 10066



VIDEO

Fiberglass rod
Ø 6 mm

[Click here
Video](#)

[Click here
Productinformation](#)

Detailed images:

All steel cages are equipped with a lateral locking brake and the new double run-out system (quick outlet and automatic run-out brake)

Quick run with rollers

automatic run-out brake

BEGINNING

RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

Achtung!
Stromleitend
Attention!
electric
conductive

DATA				
ITEM NO.	10060	10062	10064	10066
LENGTH	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	6,909	7,109	7,309	7,709
DIMENSION	H 548 / B 675 / T 250			
MATERIAL	Fiberglass core with PP sheath			
PIPE Ø	for tube diameter 40 - 100 mm			
TOTAL BREAKING LOAD	320 kg			

- ADVANTAGES**
- ✓ incl. steel reel
 - ✓ **Double run-out system**
(automatic run-out brake and fast run-out)
 - ✓ **Additional parking brake**
 - ✓ **Glass fibre rod total breaking load up to 2200 kg**
 - ✓ **Total breaking load 320 kg**
 - ✓ **Bending radius 168 mm**

Rec. tube diameter, bending radius and total breaking load for the fiberglass rod Ø 6 mm

Ø				
6 mm	40 - 100 mm	168 mm	2200 kg	320 kg

DESCRIPTION

Standard set glass-fibre rod Ø 6 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 530 mm (galvanised/powder coated) with new, double run-out system (automatic run-out brake and fast run-out), additional parking brake. Glass fibre rod total breaking load 2200 kg, total breaking load 320 kg

Optimal field of application: for pipe diameters 40 mm - 100 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fiberglass rod Ø 6 mm Standard Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the road tip and end sleeve at the rod end

INFORMATION

Compatible with:

RUNPOCAM RC2
 Length: 10 m | 30 m | 50 m
 Item no. 10139 | 10140 | 10141

[Click here
Productinformation](#)

DATA SHEET

FIBERGLASS ROD Ø 6 MM PROFI SET

with steel cage incl. new double run-out system

Item no.: 10059 | 10061 | 10063 | 10065



VIDEO
Fiberglass rod Ø 6 mm
[Click here Video](#)

[Click here Productinformation](#)

Achtung!
Stromleitend
Attention!
electric
conductive

INCL. ACCESSORIES

Detailed image

BEGINNING

RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA				
ITEM NO.	10059	10061	10063	10065
LENGTH	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	7,820	8,020	8,220	8,620
DIMENSION	H 570 / B 675/ T 250			
MATERIAL	Fiberglass core with PP sheath			
PIPE Ø	for tube diameter 40 - 100 mm			
TOTAL BREAKING LOAD	320 kg			

- ADVANTAGES**
- ✓ incl. steel reel
 - ✓ **Double run-out system**
(automatic run-out brake and fast run-out)
 - ✓ **Additional parking brake**
 - ✓ **Glass fibre rod total breaking load up to 2200 kg**
 - ✓ **Total breaking load 320 kg**
 - ✓ **Bending radius 168 mm**

Rec. tube diameter, bending radius and total breaking load for the fiberglass rod Ø 6 mm

Ø				
6 mm	40 - 100 mm	168 mm	2200 kg	320 kg

DESCRIPTION

Professional set glass-fibre rod Ø 6 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 530 mm (galvanised/powder coated) with new, double run-out system (automatic run-out brake and fast run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 2200 kg, total breaking load 320 kg

Optimal field of application: for pipe diameters 40 mm - 100 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fibreglass rod Ø 6 mm Profi Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the road tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller

INFORMATION

Compatible with:
RUNPOCAM RC2
Length: 10 m | 30 m | 50 m
Item no. 10139 | 10140 | 10141

[Click here Productinformation](#)